

End Mills

Micrograin Solid Carbide - TiAlN-FUTURA Coated

2 Flute - Double End - Stub Length - Plain Shank



Tolerance of Cutting Diameter 0/-0.0012

- Designed for slotting, drilling, pocketing and general operation
- Suitable for cutting hardened and high alloy steels, steel casting, chill casting, malleable cast iron, CrNi-steels, brass, copper, aluminum with a high percentage of silicon and abrasive plastics

Cutter Diameter (Inch)	Shank Diameter (Inch)	Length of Cut (Inch)	Overall Length (Inch)	Code	Cutter Diameter (Inch)	Shank Diameter (Inch)	Length of Cut (Inch)	Overall Length (Inch)	Code
1/32	1/8	1/16	1-1/2	935429	3/16	3/16	3/8	2	935459
3/64	1/8	3/32	1-1/2	935432	13/64	1/4	1/2	2-1/2	935462
1/16	1/8	1/8	1-1/2	935435	7/32	1/4	1/2	2-1/2	935465
5/64	1/8	1/8	1-1/2	935438	15/64	1/4	1/2	2-1/2	935468
3/32	1/8	3/16	1-1/2	935441	1/4	1/4	1/2	2-1/2	935471
7/64	1/8	3/16	1-1/2	935444	5/16	5/16	1/2	2-1/2	935474
1/8	1/8	1/4	1-1/2	935447	3/8	3/8	9/16	2-1/2	935477
9/64	3/16	5/16	2	935450	7/16	7/16	9/16	2-3/4	935480
5/32	3/16	5/16	2	935453	1/2	1/2	5/8	3	935483
11/64	3/16	5/16	2	935456					

Micrograin Solid Carbide

2 Flute - Double Ball End - Stub Length - Center Cut



Diameter (Inch)	Shank Diameter (Inch)	Flute Length (Inch)	Overall Length (Inch)	Code	Diameter (Inch)	Shank Diameter (Inch)	Flute Length (Inch)	Overall Length (Inch)	Code
1/32	1/8	1/16	1-1/2	932403	13/64	1/4	1/2	2-1/2	932437
3/64	1/8	1/8	1-1/2	932406	7/32	1/4	1/2	2-1/2	932440
1/16	1/8	1/8	1-1/2	932409	15/64	1/4	1/2	2-1/2	932443
5/64	1/8	1/8	1-1/2	932412	1/4	1/4	1/2	2-1/2	932446
3/32	1/8	3/16	1-1/2	932415	9/32	5/16	1/2	2-1/2	932449
7/64	1/8	3/16	1-1/2	932418	5/16	5/16	1/2	2-1/2	932452
1/8	1/8	1/4	1-1/2	932421	11/32	3/8	9/16	2-1/2	932455
9/64	3/16	5/16	2	932424	3/8	3/8	9/16	2-1/2	932458
5/32	3/16	5/16	2	932428	7/16	7/16	5/8	2-3/4	932461
11/64	3/16	5/16	2	932431	1/2	1/2	5/8	3	932463
3/16	3/16	3/8	2	932434					