

Boring Bars – Boring & Facing (continued)



High Speed Steel & Carbide

2 Piece Style ECS



Head and shank sold separately


Tool No.	B Minimum Bore (mm)	S Shank Diameter (mm)	HSS Head		Carbide Head		Shank
			L Length (mm)	Code	L Length (mm)	Code	Code
3	17	10	-	-	-	-	500202
3	17	12	-	-	-	-	500203
4	21	13	230	500058	230	500085	500204
5	24	15	260	500059	260	500086	500205
6	28	17	280	500060	280	500087	500206
7	31	19	310	500061	310	500088	500207
8	34	20	330	500062	330	500089	500208
9	37	22	360	500063	360	500090	500209
10	42	25	390	500064	390	500091	500210
11	50	30	430	500065	430	500092	500211
12	60	35	500	500066	500	500093	500212

Threading Bars – 60° Threading



High Speed Steel & Carbide

Single Piece Style GWS



Tool No.	B Minimum Bore (mm)	S Shank Diameter (mm)	HSS Regular Length		HSS Long Length		Carbide	
			L Length (mm)	Code	L Length (mm)	Code	L Length (mm)	Code
000	5	8	46	500102	59	500122	46	500129
00	6.5	8	50	500103	64	500123	50	500130
0	9	8	52	500104	-	-	64	500131
1	11	8	56	500105	70	500124	70	500132
2	13	8	64	500106	80	500125	80	500133

BORING BARS