

Rectangular Magnetic Chucks



Standard Pole

- These chucks are primarily designed for grinding operations
- Will effectively clamp all workpiece thicknesses down to 3mm
- Used for all general grinding applications

Fine Pole

- These chucks are ideally suited for small or thin workpieces

Standard Pole

W (mm)	L (mm)	Height (mm)	Weight (kg)	Code	W (mm)	L (mm)	Height (mm)	Weight (kg)	Code
100	180	50	8.0	381020	150	350	50	21.5	381023
130	250	50	14.0	381021	200	600	50	50.0	381025
150	300	50	18.5	381022					

Fine Pole

W (mm)	L (mm)	Height (mm)	Weight (kg)	Code	W (mm)	L (mm)	Height (mm)	Weight (kg)	Code
100	180	50	8.0	381030	150	350	50	21.5	381033
130	250	50	14.0	381031	150	450	50	27.5	381034
150	300	50	18.5	381032	200	600	50	50.0	381035

Circular Magnetic Chucks



Standard Pole

- Pole spacing = 4.0 mm steel – 2 mm brass
Force = 80N/cm²

Fine Pole

- Pole spacing = 1.5 mm steel – 0.5 mm brass
Force = 80N/cm²

Standard Pole

Diameter (mm)	Height (mm)	Weight (kg)	Code	Diameter (mm)	Height (mm)	Weight (kg)	Code
100	50	3.0	381050	255	50	16.0	381054
125	50	5.0	381051	310	50	24.0	381055
160	50	7.5	381052	350	50	27.0	381056
195	50	11.0	381053				

Fine Pole

Diameter (mm)	Height (mm)	Weight (kg)	Code	Diameter (mm)	Height (mm)	Weight (kg)	Code
100	50	3.0	381060	255	50	16.0	381064
125	50	5.0	381061	310	50	24.0	381065
160	50	7.5	381062	350	50	27.0	381066
195	50	11.0	381063				