

Keyless Drill Chucks with Locking Mechanism

LLAMBRICH

Plastic Body & Carbide Jaw Inserts



- With a locking mechanism, no key is required for closing or opening, for hammer drilling and also screwdriver operations
- Carbide jaw inserts (for 13mm capacity) reduce bit slippage and enhance wear resistance
- Ergonomic design, using materials that eliminate the possibility of rust
- With through hole for clockwise and counter-clockwise rotation
- Supplied with screw M5 (R-3/8") or M6 (R-1/2") to fix chuck to drilling machine
- Fits any type of drill (up to 1000W) via UNF thread, male and female
- Wide range of accessories

Model	Capacity (mm)	Capacity (Inch)	Mount	Diameter (mm)	Length Closed (mm)	Length Open (mm)	Weight (g)	Code
CPX-13 R-3/8	2-13	1/16-1/2	3/8" x 24 UNF	42	65	75	280	348138

Precision Keyless Drill Chucks



Capacity (Inch)	Mount	Code
0 - 1/4	J1	354100
0 - 1/4	3/8-24	354102
0 - 3/8	J2	354106
0 - 3/8	3/8-24	354108
1/32 - 1/2	J6	354112
1/32 - 1/2	J33	354114
1/32 - 1/2	1/2-20	354116
1/8 - 5/8	J6	354120
1/8 - 5/8	5/8-16	354122

Super Precision Keyless Drill Chucks

LLAMBRICH



- Maximum total integrated run-out of 0.04mm
- Self-tightening feature automatically increases gripping force in proportion to increased torque to prevent tool shank slippage (for right-hand rotation applications only)
- Permits use on high accuracy drill presses, jig borers, milling machines and production drilling equipment
- All components exposed to wear are completely hardened to maintain accuracy and extend chuck life
- Also available with through hole for EDM machines upon request

Model	Capacity (mm)	Capacity (Inch)	Mount	Diameter (mm)	Length Closed (mm)	Length Open (mm)	Weight (g)	Code
SP-1.5 J-0	0.2-1.5	0.0008-1/16	J-0	19.4	35	37.3	80	827841
SP-03 J-0	0.3-3	1/64-1/8	J-0	24.5	44	47.5	200	827842
SP-03 J-1	0.3-3	1/64-1/8	J-1	24.5	44	47.5	200	827843
SP-06 J-1	0.3-6.5	1/64-1/4	J-1	33	62	70	360	351099
SP-08 J-1	0.3-8	1/64-5/16	J-1	38	67	74	460	351100
SP-08 J-25	0.3-8	1/64-5/16	J-25	38	67	74	460	351102
SP-10 J-2	0.5-10	1/32-3/8	J-2	43	81	89	720	351104
SP-10 J-33	0.5-10	1/32-3/8	J-33	43	81	89	720	351106
SP-13 J-2	1-13	1/32-1/2	J-2	49	91	103	1,000	351108
SP-13 J-33	1-13	1/32-1/2	J-33	49	91	103	1,000	351110
SP-13 J-6	1-13	1/32-1/2	J-6	49	91	103	1,000	351112
SP-16 J-6	3-16	1/8-5/8	J-6	55	95	107	1,320	351114