

Milling Machine Adapters

- Shanks are produced according to AT3 specifications
- Made of alloy forged steel for long, durable service life
- Hardened to 56-60 HRC and ground to ensure maximum accuracy
- Taper seat T.I.R. <0.0004"

For Changing from ISA (NMTB) Shank to a Smaller ISA (NMTB)

Shank	ISA Hole	Weight (lbs)	Code
ISA40	ISA30	1.76	827171
ISA50	ISA30	4.52	827172
ISA50	ISA40	3.86	827173



For Changing from R8 Shank to MT Socket

Shank	Morse Taper Hole	Weight (lbs)	Draw Bar Thread	Code
R8	MT2	0.71	7/16 - 20	827174
R8	MT3	0.86	7/16 - 20	827175



For Changing from ISA (NMTB) Shank to MT Socket

Shank	Morse Taper Hole	Weight (lbs)	Draw Bar Thread	Code
ISA40	MT2	1.98	5/8 - 11	827176
ISA40	MT3	2.20	5/8 - 11	827177
ISA40	MT4	3.09	5/8 - 11	827178
ISA40	MT5	7.06	5/8 - 11	827179
ISA50	MT2	9.26	1 - 8	827180
ISA50	MT3	9.26	1 - 8	827181
ISA50	MT4	8.16	1 - 8	827182
ISA50	MT5	6.61	1 - 8	827183



For Changing from ISA (NMTB) Shank to R8 Socket

- Adapters are provided with the screw (Inside) to hold tools with 7/16-20 R8 shank
- To hold adapter in the spindle use draw bar with standard thread

Shank	Hole	Weight (lbs)	Draw Bar Thread	Code
ISA40	R8	3.26	5/8 - 11	827184
ISA50	R8	7.28	1 - 8	827185



For Changing from ISA (NMTB) Shank to MT Socket

- Open end type for threaded shank tools

Shank	Morse Taper Hole	Weight (lbs)	Code
ISA40	MT2	1.30	827186
ISA40	MT3	1.15	827187
ISA40	MT4	1.26	827188
ISA50	MT3	5.29	827189
ISA50	MT4	4.74	827190
ISA50	MT5	5.84	827191

