

Bore Gages

Electronic Bore Gage



- Indicator resolution: 0.0005"/0.002mm
- Indicator range: 0-0.5"/0-10mm
- Indicator has rotary face, digital/analog display, auto power off
- Ceramic contact moving tip and anvils
- CR2032 battery
- Supplied in fitted storage case



Anvil D - Ceramic Tip

| Range (Inch/mm) | Depth (Inch/mm) | Anvil Type | Code |
|-----------------|-----------------|------------|--------|
| 2-6/50-100 | 6/150 | D | 816194 |

Precision Dial Bore Gages



- Indicator graduation: 0.0001"/0.001mm
- Indicator range: 0-0.05"/0-1mm
- Shock proof dial indicator
- Style A: Steel moving tip and steel fixed Anvil
- Style B and C: Steel moving tip and ceramic fixed anvil
- Style D: Ceramic moving tip and ceramic fixed anvil
- Supplied in fitted storage case



Inch

| Range (Inch) | Depth (Inch) | Bezel Diameter (Inch) | Anvil Type | Code |
|--------------|--------------|-----------------------|------------|--------|
| 0.24-0.4 | 1.57 | 2.28 | A | 282945 |
| 0.4-0.7 | 4 | 2.28 | B | 282946 |
| 0.7-1.5 | 6 | 2.28 | C | 282947 |
| 1.4-2.4 | 6 | 2.28 | D | 282948 |
| 2-4 | 6 | 2.28 | D | 282949 |
| 2-6 | 6 | 2.28 | D | 282950 |
| 6-10 | 16 | 2.28 | D | 282951 |
| 10-16 | 16 | 2.28 | D | 282952 |

Metric

| Range (mm) | Depth (mm) | Bezel Diameter (mm) | Anvil Type | Code |
|------------|------------|---------------------|------------|--------|
| 6-10 | 40 | 58 | A | 282937 |
| 10-18 | 100 | 58 | B | 282938 |
| 18-35 | 150 | 58 | C | 282939 |
| 35-50 | 150 | 58 | D | 282940 |
| 50-100 | 150 | 58 | D | 282941 |
| 50-160 | 150 | 58 | D | 282942 |
| 160-250 | 250 | 58 | D | 282943 |
| 250-450 | 250 | 58 | D | 282944 |