



Boring Bars

S-SCLCR/L for 80° Rhombic CC__ Inserts



APPLICABLE INSERT



RIGHT HAND SHOWN

- Coolant-Thru Miniature Boring Bars: 1/4"-5/8" shank diameter

Right Hand

Type SCLCR/L	Ød (Inch)	L (Inch)	ØD (Inch)	F (Inch)	Applicable Inserts	Code
A06F-06	0.250	3.15	0.375	0.177	CC_21.5	533001
A10J-06	0.375	4.30	0.600	0.275	CC_21.5	533002
A12K-06	0.500	5.00	0.750	0.354	CC_21.5	533003
A16M-06	0.625	6.00	0.875	0.433	CC_21.5	533004
A12K-09	0.500	5.00	0.750	0.354	CC_32.5	533006
A16M-09	0.625	6.00	0.875	0.433	CC_32.5	533007

Left Hand

Type SCLCR/L	Ød (Inch)	L (Inch)	ØD (Inch)	F (Inch)	Applicable Inserts	Code
A06F-06	0.250	3.15	0.375	0.177	CC_21.5	533011
A10J-06	0.375	4.30	0.600	0.275	CC_21.5	533012
A12K-06	0.500	5.00	0.750	0.354	CC_21.5	533013
A16M-06	0.625	6.00	0.875	0.433	CC_21.5	533014
A12K-09	0.500	5.00	0.750	0.354	CC_32.5	533016
A16M-09	0.625	6.00	0.875	0.433	CC_32.5	533017

Accessories

Screw



For Type SCLCR/L	Code
A06F-06, A10J-06, A12K-06, A16M-06	210354
A12K-09, A16M-09	210351



Torx® Key

For Type SCLCR/L	Torx® Key	Code
A06F-06, A10J-06, A12K-06, A16M-06	T8	718402
A12K-09, A16M-09	T15	302319