

Saw Arbors

- Hardened and precisely ground
- Rigid arbors with extended length can reach areas that standard short arbors cannot
- Each arbor is ground for precision within 0.002" on diameter and 0.0004" T.I.R. (see drawing and table)
- Super low profile cup allows cutter to get closer to working area
- · Plug style cup gives extra support and rigidity when working with larger diameter saws

| 0.002" T.I.R. | 0. | .002" | T.I.R. | |
|---------------|----|-------|--------|--|
|---------------|----|-------|--------|--|

| d Shank Diameter (Inch) | D Hole Size (Inch) | d1 (Inch) | L (Inch) | Code | d Shank Diameter (Inch) | D Hole Size (Inch) | d1 (Inch) | L (Inch) | Code |
|----------------------------------|-----------------------------|--------------|-------------|--------|----------------------------------|-----------------------------|--------------|-------------|--------|
| 0.500 | 0.250 | 0.500 | 2.700 | 602362 | 0.750 | 0.625 | 1.000 | 3.530 | 602366 |
| 0.500 | 0.375 | 0.625 | 2.880 | 602363 | 0.750 | 1.000 | 1.500 | 3.780 | 602367 |
| 0.500 | 0.500 | 0.750 | 3.070 | 602364 | 0.750 | 1.250 | 1.750 | 4.030 | 602368 |
| - | 3-Piece Set | - | - | 602365 | - | 3-Piece Set | - | - | 602369 |

0.0004" T.I.R.

| d Shank Diameter (Inch) | D Hole Size (Inch) | d1 (Inch) | L (Inch) | Code | d Shank Diameter (Inch) | D Hole Size (Inch) | d1 (Inch) | L (Inch) | Code |
|----------------------------------|-----------------------------|--------------|-------------|--------|----------------------------------|-----------------------------|--------------|-------------|--------|
| 0.500 | 0.250 | 0.500 | 2.700 | 602370 | 0.750 | 0.625 | 1.000 | 3.530 | 602374 |
| 0.500 | 0.375 | 0.625 | 2.880 | 602371 | 0.750 | 1.000 | 1.500 | 3.780 | 602375 |
| 0.500 | 0.500 | 0.750 | 3.070 | 602372 | 0.750 | 1.250 | 1.750 | 4.030 | 602376 |
| - | 3-Piece Set | - | - | 602373 | - | 3-Piece Set | - | - | 602377 |

Weldon and R8 Shanks



- Rigid and precision design
- This versatile arbor offers flexibility in sawing operations
- The spring loaded mechanism accepts saw blades with hole diameters from 1/2" to 1"
- The saw blades are firmly secured in position with a hex socket screw
- Rust resistant, black oxide finish
- Arbors are provided with one hex wrench and one screw

| Shank Size | Hole Sizes Overall (Inch) (Inch) | | Code | Shank Size | Hole Sizes (Inch) | Overall Length (Inch) | Code |
|-------------|-------------------------------------|--------|--------|------------|-----------------------|-----------------------------|--------|
| 1/2" Weldon | 1/2, 5/8, 3/4, 7/8, 1 | 2-9/16 | 417170 | R8 | 1/2, 5/8, 3/4, 7/8, 1 | 5-3/32 | 602378 |

262