

Turning Inserts TCMT HR for Roughing




Coated Grades - CVD

YBM251

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
TCMT-3(2.5)2-HR	TCMT-16T308-HR	0.650	0.375	0.156	0.173	0.031	575254
TCMT-432-HR	TCMT-220408-HR	0.866	0.500	0.187	0.217	0.031	575260

To be used with holders: STACR/L; STFCR/L; STGCR/L; STTCR/L; S_ _-STFCR/L





EXAMPLE: STACR



TPMR General Purpose



POSITIVE TRIANGULAR



TPMR

Coated Grades - CVD

YBC151

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
TPMR-221	TPMR-110304	0.433	0.250	0.125	0.000	0.016	575578
TPMR-222	TPMR-110308	0.433	0.250	0.125	0.000	0.031	575586
TPMR-321	TPMR-160304	0.650	0.375	0.125	0.000	0.016	575594
TPMR-322	TPMR-160308	0.650	0.375	0.125	0.000	0.031	575604

YBC251

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
TPMR-221	TPMR-110304	0.433	0.250	0.125	0.000	0.016	575580
TPMR-222	TPMR-110308	0.433	0.250	0.125	0.000	0.031	575588
TPMR-321	TPMR-160304	0.650	0.375	0.125	0.000	0.016	575596
TPMR-322	TPMR-160308	0.650	0.375	0.125	0.000	0.031	575606

YBC351

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
TPMR-221	TPMR-110304	0.433	0.250	0.125	0.000	0.016	575582
TPMR-222	TPMR-110308	0.433	0.250	0.125	0.000	0.031	575590
TPMR-321	TPMR-160304	0.650	0.375	0.125	0.000	0.016	575598
TPMR-322	TPMR-160308	0.650	0.375	0.125	0.000	0.031	575608

YBM251

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
TPMR-221	TPMR-110304	0.433	0.250	0.125	0.000	0.016	575584
TPMR-222	TPMR-110308	0.433	0.250	0.125	0.000	0.031	575592
TPMR-321	TPMR-160304	0.650	0.375	0.125	0.000	0.016	575600
TPMR-322	TPMR-160308	0.650	0.375	0.125	0.000	0.031	575610