

Boring Bars

Super-Lock

Regular Length

- No special components
- The only replacement part is a cap screw
- Insert is held rigidly by unique clamp design
- Uses standard 1/4" and 3/8" I.C. triangle inserts
- A wide variety of shank sizes and lengths available

Minimum Bore (Inch)	Bore Distance (Inch)	Distance Across Flats (Inch)	Shank Diameter (Inch)	Overall Length (Inch)	Insert Size I/C (Inch)	Code
1/2	1-1/2	7/16	1/2	3	1/4	311372
1/2	2-1/4	7/16	1/2	3-3/4	1/4	311373
9/16	1-3/4	7/16	1/2	3-1/4	1/4	311374
9/16	2-5/8	7/16	1/2	4-1/8	1/4	311375
5/8	2	7/16	1/2	3-1/2	1/4	311376
5/8	3	7/16	1/2	4-1/2	1/4	311377
1/2	1-1/2	9/16	5/8	3-1/4	1/4	311378
1/2	2-1/4	9/16	5/8	4	1/4	311379
5/8	2	9/16	5/8	3-3/4	1/4	311380
5/8	3	9/16	5/8	4-3/4	1/4	311381
3/4	2-1/2	9/16	5/8	4-1/2	3/8	311382
3/4	3-3/4	9/16	5/8	5-1/2	3/8	311383
1/2	1-1/2	5/8	3/4	3-1/2	1/4	311384
1/2	2-1/4	5/8	3/4	4-1/4	1/4	311385
5/8	2	5/8	3/4	4	1/4	311386
5/8	3	5/8	3/4	5	1/4	311387
3/4	2-3/4	5/8	3/4	4-1/2	3/8	311388
3/4	3-3/4	5/8	3/4	5-3/4	3/8	311389
13/16	3	5/8	3/4	5	3/8	311390
13/16	4-1/2	5/8	3/4	6-1/2	3/8	311391



Boring Bar Sets

- Sets include C6 carbide inserts
- Supplied in wooden block



1/2" Shank - 6-Piece Set

Code
311398

5/8" Shank - 6-Piece Set

Code
311399

3/4" Shank - 8-Piece Set

Code
311400