Digimatic Height Gages

Mitutoyo

Standard Type

- Resolution: 0.0005"/0.01mm (0.0002"/0.005mm switchable)
- Easy-to-use standard type
- Carbide-tipped scriber is provided
- · Double-column structure ensures high measuring accuracy
- · Coarse/fine feed switching
- Switchable resolution
- · Two preset reference heights

Multi-Function Type with SPC Data Output

- Resolution: 0.0005"/0.01mm (0.0002"/0.005mm switchable)
- · Highly versatile multi-function type
- · Carbide-tipped long scriber is provided
- · Rigid construction ensures repeatable measurement
- Switchable resolution
- · Coarse/fine feed switching
- SPC data output
- Two preset reference heights

Bi-directional touch-signal probe is an optional accessory. It can quickly and accurately measure steps, and inside and outside widths.

Standard Multi-Function

Standard

Range (Inch/mm)	Accuracy (Inch)	Weight (kg)	Code
0-12/0-300	±001	4.7	192-630-10
0-18/0-450	±002	7.5	192-631-10
0-24/0-600	±002	8.3	192-632-10

Multi-Function

Range (Inch/mm)	Accuracy (Inch)	Weight (kg)	Code
0-12/0-300	±001	5.7	192-670-10
0-18/0-450	±0015	7.5	192-671-10
0-24/0-600	±0015	8.3	192-672-10

Multi-Beam Dial Height Gages



- Graduation: 0.001"
- Counter readout: 0.1"
- Carbide-tipped scriber, stainless steel beam and base, with driving wheel for vertical movement
- DIN862
- · Indicator holder is optional
- Supplied in fitted storage case

Range (Inch)	Number of Beams	Code
0-12	2	280769
0-18	2	280770
0-24	2	280772
0-40	3	280773



BAR