



## Shock Proof Dial Indicator

Metric

- Meets DIN878 standard
- Graduation: 0.01mm
- Bezel diameter: 58mm
- Stem diameter: 8mm
- Shock proof, jeweled
- Satin chrome plated steel body
- Lug back
- With tolerance index
- Contact point thread M2.5 x 0.45
- Supplied in fitted storage case

Range (mm)	Code
0-10	282676



## Dial Indicators

Metric

- Meets DIN878 standard
- Graduation: 0.01mm
- Bezel diameter: 58mm
- Stem diameter: 8mm
- Jeweled
- Satin chrome plated steel body
- With tolerance index
- Contact point thread M2.5 x 0.45
- Supplied in fitted storage case

Type	Range (mm)	Code
Lug Back	0-30	282665
Flat Back	0-30	282664



## Dial Indicators

Range (Inch)	Bezel Diameter (Inch)	Reading	Code
0-1	2-3/16	0-100-0	841021



## Short Range Dial Indicators

Metric

- Meets DIN878 standard
- Graduation: 0.01mm
- Bezel diameter: 58mm
- Stem diameter: 8mm
- Jeweled
- Satin chrome plated steel body
- With tolerance index
- Contact point thread M2.5 x 0.45
- Supplied in fitted storage case

Type	Range (mm)	Code
Flat Back	0-10	282660
Lug Back	0-10	282663

