

Re-Nu Thread Inserts

Metric Internal/Metric External

Steel - Black Oxide Finish (Nylon Pellet Locking Element)

Internal Thread 6H (2B)	External Thread 6g (2A)	Length (mm)	Length (Inch)	*Tap Drill Size	Tap Drill Size (mm)	Code
M3 x 0.50	M6 x 1.00	6.5	0.256	#9	5.00	718577
M4 x 0.70	M8 x 1.25	7.5	0.296	H	6.75	718578
M5 x 0.80	M8 x 1.25	7.5	0.296	H	6.75	718579
M6 x 1.00	M10 x 1.50	10.5	0.414	Q	8.50	718580
M8 x 1.25	M12 x 1.75	12.5	0.493	Y	10.00	718581
M10 x 1.50	M16 x 2.00	17.0	0.670	35/64	14.00	718582
M12 x 1.75	M16 x 2.00	17.0	0.670	35/64	14.00	718583
M14 x 2.00	M20 x 2.50	18.0	0.709	11/16	17.50	718584
M16 x 2.00	M24 x 3.00	20.0	0.788	53/64	21.00	718585

Metric Class 6H/6g threads are suitable for applications where inch series class 2A/2B were used.

* Closest inch drill approximately 75% thread