


Electronic Indicators



Compact



- Meets ASME B89.1.10M-2001 standards
- Button function:
 - inch/mm: .. short press for inch/metric conversion
 - long press to change measuring direction
 - ABS: short press for absolute/incremental measurement
 - long press to preset data
 - O/ON:..... short press to turn on when power is off
 - long press to turn off
- Keep preset data in memory after restart
- Battery CR1632 – auto power off
- Data output
- Flat back
- Contact point thread #4-48UNF
- Supplied in fitted storage case




Range (Inch/mm)	Accuracy (Inch)	Resolution (Inch/mm)	Hysteresis (Inch)	INSIZE No.	Code
0.2/5	±0.0015	0.0005/0.01	0.0005	2114-5FE	877131
0.2/5	±0.00015	0.00005/0.001	0.00005	2114-5IFE	877130

Dial Indicators



Compact

- Meets ASME B89.1.10M-2001 standards
- Lug back
- Supplied with limit pointers and bezel clamp
- Supplied in fitted storage case



Range (Inch)	Accuracy (Inch)		Graduation	Range/rev.	Dial Reading	INSIZE No.	Code
	First 2.5 rev.	Overall					
0.1	-	±0.001	0.001	0.1	0-100	2304-01	282699
0.2	-	±0.001	0.001	0.1	0-100	2304-02	282700
0.25	±0.001	±0.001	0.001	0.1	0-100	2304-025	282701
0.1	-	±0.0005	0.0005	0.05	0-50	2304-015	282702
0.2	±0.0005	±0.0015	0.0005	0.05	0-50	2304-0205	282703
0.25	±0.0005	±0.0015	0.0005	0.05	0-50	2304-0255	282704

Flat back

Range (Inch)	Accuracy (Inch)		Graduation	Range/rev.	Dial Reading	INSIZE No.	Code
	First 2.5 rev.	Overall					
0.2	-	±0.001	0.001	0.1	0-100	2304-02F	877298