


Boring Bars

S-SCLCR/L for 7° Positive 80° Rhombic CC__ Inserts



APPLICABLE INSERT



RIGHT HAND SHOWN

Right Hand

Type S-SCLCR/L	Ød (Inch)	L (Inch)	ØD (Inch)	F (Inch)	Applicable Inserts	Code
4-2	0.315	4	0.354	0.188	CC 21.5	534301
6-2	0.375	6	0.468	0.250	CC 21.5	534302
8-2	0.500	7	0.560	0.290	CC 21.5	534303
8-3	0.500	7	0.600	0.312	CC 32.5	534304
10-3	0.625	8	0.866	0.406	CC 32.5	534305
12-3	0.750	10	0.920	0.500	CC 32.5	534306
16-3	1.000	12	1.120	0.609	CC 32.5	534307

Left Hand

Type S-SCLCR/L	Ød (Inch)	L (Inch)	ØD (Inch)	F (Inch)	Applicable Inserts	Code
4-2	0.315	4	0.354	0.188	CC 21.5	534311
6-2	0.375	6	0.468	0.250	CC 21.5	534312
8-2	0.500	7	0.560	0.290	CC 21.5	534313
8-3	0.500	7	0.600	0.312	CC 32.5	534314
10-3	0.625	8	0.866	0.406	CC 32.5	534315
12-3	0.750	10	0.920	0.500	CC 32.5	534316
16-3	1.000	12	1.120	0.609	CC 32.5	534317

Accessories

Screw



For Type S-SCLCR/L	Code
4-2	210354
6-2, 8-2	210350
8-3, 10-3, 12-3, 16-3	210351



Torx® Key

For Type S-SCLCR/L	Torx® Key	Code
4-2, 6-2, 8-2	T7	549505
8-3, 10-3, 12-3, 16-3	T15	302319