

Threading

Threading Inserts - Carbide - Partial Profile 60°



External and Internal Ground Form

External Ground Form

L mm I.C. (Inch)	Pitch TPI	External RH	Grade	Code
11 (1/4)	48-16	11 ER A60	MXC	578002
16 (3/8)	48-16	16 ER A60	MXC	578008
16 (3/8)	14-8	16 ER G60	MXC	578014
16 (3/8)	48-8	16 ER AG60	MXC	578020
22 (1/2)	7-5	22 ER N60	MXC	578026
11 (1/4)	48-16	11 ER A60	P25C	578004
16 (3/8)	48-16	16 ER A60	P25C	578010
16 (3/8)	14-8	16 ER G60	P25C	578016
16 (3/8)	48-8	16 ER AG60	P25C	578022
22 (1/2)	7-5	22 ER N60	P25C	578028
11 (1/4)	48-16	11 ER A60	BMA	578000
16 (3/8)	48-16	16 ER A60	BMA	578006
16 (3/8)	14-8	16 ER G60	BMA	578012
16 (3/8)	48-8	16 ER AG60	BMA	578018
22 (1/2)	7-5	22 ER N60	BMA	578024

Internal Ground Form

L mm I.C. (Inch)	Pitch TPI	Internal RH	Grade	Code
11 (1/4)	48-16	11 IR A60	MXC	578032
16 (3/8)	48-16	16 IR A60	MXC	578040
16 (3/8)	14-8	16 IR G60	MXC	578046
16 (3/8)	48-8	16 IR AG60	MXC	578052
22 (1/2)	7-5	22 IR N60	MXC	578058
11 (1/4)	48-16	11 IR A60	P25C	578034
16 (3/8)	48-16	16 IR A60	P25C	578042
16 (3/8)	14-8	16 IR G60	P25C	578048
16 (3/8)	48-8	16 IR AG60	P25C	578054
22 (1/2)	7-5	22 IR N60	P25C	578060
11 (1/4)	48-16	11 IR A60	BMA	578030
16 (3/8)	48-16	16 IR A60	BMA	578038
16 (3/8)	14-8	16 IR G60	BMA	578044
16 (3/8)	48-8	16 IR AG60	BMA	578050
22 (1/2)	7-5	22 IR N60	BMA	578056