


Permanent and Welding Magnets

Permanent Magnets Magnetic Strips



- Material: Strontium Ferrite
- Supplied in sheet, strip and adhesive backed finishes
- Can be cut with scissors
- Can be used in temperatures up to 176°F

Plain - Flexible Magnetic Strip

Width (mm)	Thickness (mm)	Length (m)	Code	Width (mm)	Thickness (mm)	Length (m)	Code
9.5	3.6	10	381170	15.0	6.4	10	381172
11.0	4.6	10	381171	9.5	3.6	2	381173

Adhesive Backed Flexible Magnets

Width (mm)	Thickness (mm)	Length (mm)	Code	Width (mm)	Thickness (mm)	Length (mm)	Code
7.5	0.75	10	381175	13.0	0.50	1	381178
12.5	0.75	10	381176	9.5	3.60	150	381179
20.0	0.75	10	381177	150 sq.	0.75	150 sq.	381180

Welding Magnets Mitre Clamps



- Provides effective and inexpensive method of clamping components
- Mitre clamps provide the welder with a simple means of clamping flat or round ferrous components

Length of Base Face (Inch)	Length of Top Face (Inch)	Height (Inch)	Width (Inch)	Pull (lbs)	Code	Length of Base Face (Inch)	Length of Top Face (Inch)	Height (Inch)	Width (Inch)	Pull (lbs)	Code
6	2-3/4	1-3/4	1-5/8	250	381181	7	3-3/4	1-3/4	1-5/8	150	381182

Heavy Duty Variable Clamp



- Provides the user with the means to clamp components during welding, fabrication and assembly applications with the added benefit of 88 lb. clamping force, enabling larger components to be clamped with ease
- Settings from 45° to 90°

Length (Inch)	Height (Inch)	Width (Inch)	Weight (lbs)	Pull (lbs)	Code
5-1/2	5-1/2	1-3/8	3	88	381184