

End Mills - ALU-POWER

Micrograin Solid Carbide - TiCN Coated

3 Flute - 45° Helix - Regular Length

Cutting Diameter (Inch)	Shank Diameter (Inch)	Shank Style	Length of Cut (Inch)	Overall Length (Inch)	Code	Cutting Diameter (Inch)	Shank Diameter (Inch)	Shank Style	Length of Cut (Inch)	Overall Length (Inch)	Code
1/8	1/8	Plain	3/8	1-1/2	888584	7/16	7/16	Plain	1-1/4	2-3/4	888589
3/16	3/16	Plain	9/16	2	888585	1/2	1/2	Plain	1-1/4	3	888590
1/4	1/4	Plain	5/8	2-1/2	888586	5/8	5/8	Plain	1-5/8	3-1/2	888591
5/16	5/16	Plain	5/8	2-1/2	888587	3/4	3/4	Plain	1-5/8	4	888592
3/8	3/8	Plain	1	2-1/2	888588	1	1	Plain	2	5	888593

Micrograin Solid Carbide

3 Flute - 45° Helix - Extra Long Length



Tolerance of Cutting Diameter 0/-0.0005

- For high velocity milling of aluminum and other non-ferrous materials
- 3 flute and 45° helix allow harmonic balance at high speed conditions and smooth cutting
- Provides improved surface roughness
- Tightly controlled cylindrical margin
- Maximum material removal, chip evacuation, and stability

Cutting Diameter (Inch)	Shank Diameter (Inch)	Shank Style	Length of Cut (Inch)	Overall Length (Inch)	Code	Cutting Diameter (Inch)	Shank Diameter (Inch)	Shank Style	Length of Cut (Inch)	Overall Length (Inch)	Code
1/4	1/4	Plain	1-1/4	3-1/4	888419	1/2	1/2	Plain	2	4	888423
5/16	5/16	Plain	1-1/4	3-1/2	888420	5/8	5/8	Plain	2-1/2	5	888424
3/8	3/8	Plain	1-1/2	3-1/2	888421	3/4	3/4	Plain	3-1/4	6	888425
7/16	7/16	Plain	2	4	888422	1	1	Plain	3-1/4	6	888426