


Turning Inserts DNMG General Purpose



NEGATIVE 55° RHOMBIC



DNMG

Coated Grades - CVD

YBC251

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
DNMG542	DNMG190608	0.760	0.625	0.250	0.313	0.031	574170

To be used with holders: PDJNR/L; PDNNR/L; MDJNR/L; MDPPN; S_ _-PDUNR/L; S_ _-PDSNR/L; S_ _-MDUNR/L



EXAMPLE: PDJNR



DNMA No Chipbreaker

Coated Grades - CVD

YBC151

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
DNMA442	DNMA150608	0.610	0.500	0.250	0.203	0.031	574022

YBD102

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
DNMA441	DNMA150604	0.610	0.500	0.250	0.203	0.016	574016
DNMA442	DNMA150608	0.610	0.500	0.250	0.203	0.031	574024

YBD151

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
DNMA431	DNMA150404	0.610	0.500	0.187	0.203	0.016	574004
DNMA441	DNMA150604	0.610	0.500	0.250	0.203	0.016	574018
DNMA442	DNMA150608	0.610	0.500	0.250	0.203	0.031	574026

YBD152

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
DNMA441	DNMA150604	0.610	0.500	0.250	0.203	0.016	574020
DNMA442	DNMA150608	0.610	0.500	0.250	0.203	0.031	574028

To be used with holders: PDJNR/L; PDNNR/L; MDJNR/L; MDPPN; S_ _-PDUNR/L; S_ _-PDSNR/L; S_ _-MDUNR/L



EXAMPLE: PDJNR